

BOBCAT COMPANY PRICE PAGES NA Compact Tractors



Please note the following when using Bobcat Price Pages:

- All prices are shown in U.S. dollars.
- Check DealerNet Pricing Homepage for current Canadian exchange rate.
- To ensure having the correct Part Number for a Dealer Installed Accessory, obtain the loader model and serial number and check with Dealer Parts Department.
- For current Dealer Installed Accessories pricing, reference Quote & Order or Dealer Parts Department.
- Prices and specifications are subject to change without notice.

THE FOLLOWING UPDATES HAVE BEEN MADE TO THIS DOCUMENT:

Date	Description of Change
6/11/2020	Correction to p/n on mid-PTO kit for CT40xx HST
6/11/2020	Correction to p/n on Translation Kit for CT40xx
7/9/2020	Correction to operating weight of CT2540
7/9/2020	Addition of 3rd Function Aux Hydraulic Kits and cutting edges for FEL's
7/9/2020	Addition of FEL specs for appropriate platform pages
8/21/2020	Corrected turf tire size on CT40xx platform
1/4/2021	Updated pricing to reflect Jan-2021 increase
1/21/2021	Corrected Tire/Wheel Assembly part numbers and descriptions
2/5/2021	Corrected Telescopic Lower Link Accessory for CT40XX
3/23/2021	Added Tractor with Front End Loader length to specs
4/15/2021	Removed block heater from CT10xx
6/7/2021	Effective Monday, June 7th, 2021 Bobcat Company has adjusted the SLP.
7/12/2021	Added Field Cab and accessories for CT1000 and CT4000. Updated description of radio for CT2500 models.
8/17/2021	Corrected error on CT4000 standard equipment, and added Tractor width for optional tires all platforms
11/1/2021	Effective Monday, November 1st, 2021 Bobcat Company has adjusted the SLP of powered units and front end loader
11/2/2021	Corrected an error front tire size under standard equipment for CT2000, CT2500, CT4000, and CT5500
1/10/2022	Added Block Heater kit for CT1000 models
7/1/2022	Effective Friday, July 1st, 2022 Bobcat Company has adjusted the SLP of powered units and front end loader
1/2/2023	Bobcat Company has adjusted the SLP of powered units and front end loader
4/25/2024	Updated tire information for CT's, miscellaneous part number and description updates.
12/16/2024	Update tire part number and sizes. Updated miscellaneous machine specs (speed, width, height).
4/1/2025	Added CT45xx models. Updated misc. FL9 specs. Updated misc. part numbers.
11/11/2025	Added CT1025 TLB
1/1/2026	Updated pricing for carriers, FEL's and wheel tire assemblies. Added new Ind/Ag Hybrid tire option. Discontinued

**Certain Specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual Bobcat equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors.*

CT1021/CT1025

Compact Tractor



Standard Equipment

Brakes, Wet Multi Disc	Lights: Headlights, Tail Lights, Brake lights, Hazard
Cupholder	- Flashers, and Turn Signals
Draw Bar, Fixed	Mid PTO (Live)
Electric Key Shutoff	Parking Brake
Four Wheel Drive	PTO Shield
Glow Plug Engine Pre-Heat	Rear Differential Lock
Horn	Rear PTO (Live)
Hydraulic Three-Point Lift Position Control System	ROPS: Two-Post, Foldable*
Hydraulic Power Steering	Safety Interlock System
Instrumentation: Hourmeter, Tachometer, Engine	Three-Point Hitch, Category 1 Limited
- Temperature, Fuel Gauge, and Warning Lights	Tires: Industrial 18x8.5-10 - Front; 26x12-12 - Rear
Lift Rod - Turnbuckle	Vinyl Seat, w/ Retractable Seat Belt

****The CT10xx platform does not come standard with rear remote hydraulics****

* Roll Over Protective Structure (ROPS) - Meets Requirements of SAE-J1194 and Field Cab Option meets EEC 86/298

Quick Specs

	CT1021	CT1025
Engine - Tier III Compliant.....	3C100LWH-U2	3C100LFH-U1
Engine Fuel/Cooling.....	Diesel/Liquid	Diesel/Liquid
Gross Horsepower.....	21.0 hp	24.5 hp
Engine Displacement.....	61.5 cu. in.	61.5 cu. in.
PTO Horsepower.....	16.3 hp	18.8 hp
PTO RPM.....	540	540
Mid-PTO RPM (standard).....	2200	2200
Alternator Capacity.....	50 amp	50 amp
Travel Speed (Forward) w/ R-4 Ind Tires.....	11.1 mph	11.1 mph
Travel Speed (Reverse) w/ R-4 Ind Tires.....	7.6 mph	7.6 mph
Operating Weight.....	1521 lbs.	1521 lbs
Height - Top of Structure w/ R-4 Ind Tires.....	87.6 in.	87.6 in.
Transmission.....	Hydrostatic	Hydrostatic
Width w/ R-4 Ind Tires.....	45.7 in.	45.7 in.
Width w/ Ag Tires.....	45.5 in.	45.5 in.
Width w/ Turf Tires.....	45.5 in.	45.5 in.
Length w/ 3 Pt. Hitch (no weight bracket).....	99.3 in.	99.3 in.
Wheelbase.....	55.1 in.	55.1 in.
Min. Ground Clearance w/ R-4 Ind Tires.....	6.3 in.	6.3 in.
Inside Turning Radius.....	100.0 in	100.0 in.
Fuel Tank Capacity.....	6.7 gal.	6.7 gal.
3Pt Hitch Lift Cap (24" behind lift point with FEL).....	700 lbs. *	700 lbs. *
Hydraulic Pump Flow.....	6.4 gpm	6.4 gpm
Implement Flow.....	4.6 gpm	4.6 gpm
Steering Flow.....	1.8 gpm	1.8 gpm

* With front end loader installed (used as front ballast)

CT1021/CT1025**Compact Tractor****Ordering Path:**

- 1) Select Tractor Model
 - 2) Select Tire (Pricing dependent on option)
 - 3) Select Factory Installed Front End Loader (Optional)
 - 4) Select Factory Installed Backhoe (Optional - CT1025 only)
- NOTE:** If Factory Installed Backhoe is selected, FEL is required

Part Number	Description	Compact Utility Tractor	SLP in US \$
M1623	CT1021HST Compact Tractor.....		\$15,086
M1624	CT1025HST Compact Tractor.....		\$17,205

Part Number	Description	Factory Installed Options	SLP in US \$
-------------	-------------	---------------------------	--------------

Tire Options

M_-R02-C01	Ag Tire: 18 x 8.5 - 10 4PR, Front; 26 x 12 - 12 4PR, Rear.....	\$263
	<i>Superior traction in muddy & soft soil, ideal for maximum pulling power & maneuverability in rugged conditions.</i>	
M_-R02-C02	Ind Tire (Standard): 18 x 8.5 - 10 4PR, Front; 26 x 12 - 12 4PR, Rear.....	\$158
	<i>Balanced combination of traction & surface area. Ideal for optimizing traction & minimizing ground disturbance.</i>	
M_-R02-C03	Turf Tire: 18 x 8.5 - 10 4PR, Front; 26 x 12 - 12 4PR, Rear.....	\$263
	<i>Maximizes surface area for minimal ground disturbance, ideal for protecting lawn/grass & icy conditions.</i>	
M_-R02-C07	Ind/Ag Hybrid Tire: 18 x 8.5 - 10 4PR, Front; 26 x 12 - 12 4PR, Rear.....	\$296
	<i>Premium, hybrid tread which combines traction of ag tire with high surface area & ride quality of the industrial tire.</i>	

Note:**Front End Loader - Bob-Tach**

Includes quick attach front-end loader, hose kit, grille guard, mounting kit,
joystick valve and 48" Bob-Tach bucket.
(For maximum lift capacity, equip with rear ballast box)

M_-A01-C01	FL6 Factory Installed.....	\$3,787
------------	----------------------------	---------

FEL Specs

	<u>FL6</u>
Maximum Lift Height to Bucket Pivot Pin.....	72"
Clearance with Level Bucket at Maximum Lift Height.....	65"
Clearance with Bucket Dumped at Maximum Lift Height.....	50"
Reach at Maximum Lift Height.....	14"
Tractor Length with Front End Loader & 3 Pt Hitch.....	136.6"
Bucket Dump Angle at Maximum Lift Height.....	57 degrees
Maximum Rollback Angle.....	22 degrees
Lift Capacity to Maximum Height at Bucket Pivot Pins.....	608 lbs.
Loader Weight.....	606 lbs
Breakout Force at Pivot Pin.....	1554 lbs
Standard Bucket Width.....	48"
Reach with Bucket on the Ground.....	53"

Note:**BH67 BACKHOE**

Factory installed backhoe model BH67. Includes subframe, mounting hardware, hydraulic hoses & backhoe w/ integrated flip over seat. Must include factory installed Front End Loader
(Does not ship w/ 3 Point Link Group - see Parts catalog)

M_A01-C09 Factory Installed Backhoe (CT1025 Only)..... \$8,595

Backhoe Specs

	<u>BH67</u>
Digging Depth (2' flat bottom).....	73"
Reach from center line of Swing Pivot.....	100"
Loading Height (bucket at 60°).....	55"
Maximum Level Angling.....	8°
Swing Arc.....	180°
Transport Height (maximum).....	70"
Bucket Rotation	152°
Stabilizer Spread (down position).....	62"
Stabilizer Spread (up position).....	60 "
Bucket Digging Force.....	2240 lbs/ft
Dipperstick Digging Force.....	1171 lbs/ft
Operating Pressure.....	1885 psi
Shipping Weight (without bucket).....	657 lbs.

CT1021/CT1025**Compact Tractor**

Part Number	Description	Dealer Installed Accessories - Order From Parts	SLP in US \$
-------------	-------------	---	--------------

For current Dealer Installed Accessories pricing, reference BobQuote or Dealer Parts Department.

Hydraulic / Hitch Accessories			
7370398	Hydraulic Filter Guard Kit.....	\$ _____	
	Protects filter, includes guard and hardware. Install time: 0.25 hrs.		
7370400	Rear Remote Hydraulic Valve Kit.....	\$ _____	
	Includes valve, lever, couplers, hose, tube lines and hardware. Install time: 1.5 hrs.		

Ballast			
7402084	Front Weight Bracket (Not compatible with grille guard or FEL).....	\$ _____	
	Includes weight bracket and associated hardware. Install time: 0.5 hrs.		
7158255	Suitcase Weights - 50 lbs (22.8 kg)	\$ _____	
	Includes cast weight only. CT10xx can hold up to 5 weights. Bracket required.		

ROPS Accessories			
7371412	Rear Working Light Kit.....	\$ _____	
	Includes light, bracket and hardware. Install time: 0.25 hrs.		
7370404	Canopy.....	\$ _____	
	Includes canopy and hardware. Install time: 1 hrs.		
7E+06	Rear View Mirror.....	\$ _____	
	Includes mirror, bracket and hardware. Install time: 0.25 hrs.		

Tire/Wheel Assemblies			
Bias Ply Ag (R1)			
7460198	18x8.5-10 4PR R-1, Front Left.....	\$ _____	
7460199	18x8.5-10 4PR R-1, Front Right.....	\$ _____	
7460200	26x12-12 4PR R-1, Rear Left.....	\$ _____	
7460201	26x12-12 4PR R-1, Rear Right.....	\$ _____	
Bias Ply Industrial/General Purpose (R4)			
7460202	18x8.5-10 4PR R-4, Front Left.....	\$ _____	
7460203	18x8.5-10 4PR R-4, Front Right.....	\$ _____	
7460204	26x12-12 4PR R-4, Rear Left.....	\$ _____	
7460205	26x12-12 4PR R-4, Rear Right.....	\$ _____	
Bias Ply Industrial/Ag Hybrid (R14)			
46985463	18x8.5-10 4PR R-4, Front Left.....	\$ _____	
46985462	18x8.5-10 4PR R-4, Front Right.....	\$ _____	
46985466	26x12-12 4PR R-4, Rear Left.....	\$ _____	
46985465	26x12-12 4PR R-4, Rear Right.....	\$ _____	
Bias Ply Turf (R3)			
7460196	18x8.5-10 4PR R-3, Front.....	\$ _____	
7460197	26x12-12 4PR R-3, Rear.....	\$ _____	

Front-End Loader Accessories

7393027	Bolt-on 48" Cutting Edge for FL6 (CT10xx).....	\$ _____
7392239	3rd Function Kit for FL6 (CT10xx).....	\$ _____
Includes flat face couplers (Pioneer couplers need to be ordered separately). Install time: 2.0 hrs.		

Additional Accessories

7370401	Front Towing Hook Kit.....	\$ _____
Includes front hitch and hardware.		
7370403	Cruise Control Kit.....	\$ _____
Includes relay, switch, harness, cruise magnet and hardware. Install time: 0.75 hrs.		
7388810	Spark Arrestor Muffler Kit.....	\$ _____
Includes spark arrestor and hardware. Install time: 0.25 hrs.		
7481318	Block Heater.....	\$ _____
Block Heater for CT1000. Kit includes block heater and instructions. Install time: 1.5 hrs.		
7380126	Reversible Seat Kit (Required for BH66).....	\$ _____
Includes linkage and hardware. Install time: 0.5 hrs.		
7418251	Translation Kit.....	\$ _____
Includes decals, Operator's Handbook, Safety Manual, and Warranty Brochure. Install time: 0.25 hrs.		

Field Cab & Accessories

7414859	Field Cab Kit.....	\$ _____
Includes cab, turn signals, taillights, joystick extension kit, cab supports and hardware. Install time: 5.0 hrs.		
7370406	Rear Work Light Kit.....	\$ _____
Field Cab is required. Kit includes one rear work light and hardware. Install time: 1.5 hr		
7457501A	Bluetooth Radio Kit.....	\$ _____
Field Cab is required. Includes, stereo, antenna and hardware. Install time: 1.0 hrs.		
7370408	Rear Wiper Kit.....	\$ _____
Field Cab is required, Included motor, wiper arm, wiper, switch and hardware. Install time: 2.0 hrs.		
7405531	Beacon Kit for Field Cab.....	\$ _____
Requires field cab. Includes switch, wiring, hardware, beacon lamp and bracket. Install time: 1.0 hrs.		
7387011A	Interior Material Kit.....	\$ _____
Field Cab required. Noise dampening material.		
7392998	Cab Hydraulic Extension Kit.....	\$ _____
Field Cab and FEL required. Kit is required to extend the FEL joystick into field cab.		

CT2025/CT2035/CT2040

Compact Tractor



Standard Equipment

Brakes, Wet Multi Disc	Lights: Headlights, Tail Lights, Brake lights, Hazard
Cupholder	- Flashers, and Turn Signals
Draw Bar, Adjustable	Loader Joystick & Valve
Electric Key Shutoff	Parking Brake
Floor Mat	PTO Shield
Four Wheel Drive	Rear Differential Lock
Fuel Heater (excluded CT2025)	Rear PTO (Live)
Glow Plug Engine Pre-Heat	ROPS: Two-Post, Foldable*
Horn	Safety Interlock System
Hydraulic Three-Point Lift Position Control System	Three-Point Hitch, Category 1
Hydraulic Power Steering	Tires: Industrial 27X8.5-15, Front; 15-19.5, Rear
Instrumentation: Hourmeter, Tachometer, Engine	Vinyl Suspension Seat, w/ Retractable Seat Belt
- Temperature, Fuel Gauge, and Warning Lights	
Lift Rod - Turnbuckle	

****The CT20xx platform does not come standard with rear remote hydraulics****

* Roll Over Protective Structure (ROPS) - Meets Requirements of ISO12003-2 and Field Cab Option meets EEC 86/298

Quick Specs

	CT2025 HST	CT2025 MST	CT2035 HST	CT2035 MST	CT2040 HST	CT2040 MST
				<i>Discontinued</i>		<i>Discontinued</i>
Eng(CT2025 T-III, CT2035/40 T-IV).....	3A165LWH-U	3A165LWM-U	3H-TH4A	3H-TM4A	3H-TH4A	3H-TM4A
Engine Fuel/Cooling.....	Diesel/Liquid	Diesel/Liquid	Diesel/Liquid	Diesel/Liquid	Diesel/Liquid	Diesel/Liquid
Gross Horsepower.....	24.5 hp	24.5 hp	34.9 hp	34.9 hp	39.6 hp	39.6 hp
Engine Displacement.....	100 cu. in.	100 cu. in.	111.4 cu. in.	111.4 cu. in.	111.4 cu. in.	111.4 cu. in.
PTO Horsepower.....	21.8 hp	22.2 hp	29.4 hp	30.8 hp	31.9 hp	34.9 hp
PTO RPM.....	540	540	540	540	540	540
Mid-PTO RPM (optional).....	1976	1976	1988	1988	1988	1988
Alternator Capacity.....	75 amps	75 amps	75 amps	75 amps	75 amps	75 amps
Travel Speed (Forward) w/ R-4 Ind Tires.....	9.4 mph	9.2 mph	14 mph	13.8 mph	14 mph	13.8 mph
Travel Speed (Reverse) w/ R-4 Ind Tires.....	6.5 mph	6 mph	9.7 mph	9 mph	9.7 mph	9 mph
Operating Weight.....	2634 lbs.	2634 lbs.	3005 lbs.	3005 lbs.	3005 lbs.	3005 lbs.
Height - Top of Structure w/ R-4 Ind Tires.....	92.2 in.	92.2 in.	92.2 in.	92.2 in.	92.2 in.	92.2 in.
Width w/ R-4 Ind Tires.....	62.4 in.	62.4 in.	62.4 in.	62.4 in.	62.4 in.	62.4 in.
Width w/ Ag Tires.....	54.4 in.	54.4 in.	54.4 in.	54.4 in.	54.4 in.	54.4 in.
Width w/Turf Tires.....	56.6 in.	56.6 in.	56.6 in.	56.6 in.	56.6 in.	56.6 in.
Length w/ 3 Pt. Hitch (no weight bracket).....	120.9 in.	120.9 in.	120.9 in.	120.9 in.	120.9 in.	120.9 in.
Wheelbase.....	65.7 in.	65.7 in.	65.7 in.	65.7 in.	65.7 in.	65.7 in.
Min. Ground Clearance w/ R-4 Ind Tires.....	11.7 in.	11.7 in.	11.7 in.	11.7 in.	11.7 in.	11.7 in.
Inside Turning Radius.....	96.5 in.	96.5 in.	96.5 in.	96.5 in.	96.5 in.	96.5 in.
Fuel Tank Capacity.....	9.0 gal.	9.0 gal.	9.0 gal.	9.0 gal.	9.0 gal.	9.0 gal.
3Pt Hitch Lift Cap (24" behind lift point with FEL). 1631 lbs. *	1631 lbs. *	1631 lbs. *	1631 lbs. *	1631 lbs. *	1631 lbs. *	1631 lbs. *
Hydraulic Pump Flow.....	11.4 gpm	11.4 gpm	11.4 gpm	11.4 gpm	11.4 gpm	11.4 gpm
Implement Flow.....	6.9 gpm	6.9 gpm	6.9 gpm	6.9 gpm	6.9 gpm	6.9 gpm
Steering Flow.....	4.5 gpm	4.5 gpm	4.5 gpm	4.5 gpm	4.5 gpm	4.5 gpm

* With front end loader installed (used as front ballast)

CT2025/CT2035/CT2040**Compact Tractor****Ordering Path:**

- 1) Select Tractor Model
- 2) Select Tire (Pricing dependent on option)
- 3) Select Factory Installed Front End Loader (Optional)

Part Number	Description	Compact Utility Tractor	SLP in US \$
M1626	CT2025HST Compact Tractor.....		\$22,524
M1627	CT2025MST Compact Tractor.....		\$20,760
M1628	CT2035HST Compact Tractor.....		\$28,653
M1629	CT2035MST Compact Tractor (Discontinued).....		\$26,823
M1630	CT2040HST Compact Tractor.....		\$29,415
M1631	CT2040MST Compact Tractor (Discontinued).....		\$27,552

Part Number	Description	Factory Installed Options	SLP in US \$
-------------	-------------	---------------------------	--------------

Tire Options

M_-R02-C01	Ag Tire: 7-16 6PR, Front; 11.2-24 6PR, Rear.....	\$395
	<i>Superior traction in muddy & soft soil, ideal for maximum pulling power & maneuverability in rugged conditions.</i>	
M_-R02-C02	Ind Tire (Standard): 27x8.5-15 6PR, Front; 15-19.5 6PR, Rear.....	\$263
	<i>Balanced combination of traction & surface area. Ideal for optimizing traction & minimizing ground disturbance.</i>	
M_-R02-C03	Turf Tire: 27x8.5-15 6PR, Front; 41x14-20 4PR, Rear.....	\$395
	<i>Maximizes surface area for minimal ground disturbance, ideal for protecting lawn/grass & icy conditions.</i>	
M_-R02-C07	Ind/Ag Hybrid Tire: 27x8.5-15 6PR, Front; 15-19.5 6PR, Rear.....	\$592
	<i>Premium, hybrid tread which combines traction of ag tire with high surface area & ride quality of the industrial tire.</i>	

Front End Loader - Bob-Tach

Includes quick attach front-end loader, hose kit, bucket level indicator, grille guard, mounting kit, joystick valve and 60" Bob-Tach bucket. (For maximum lift capacity, equip with rear ballast box)

M_-A01-C01	FL7 Factory Installed (CT2025 Only).....	\$5,009
M_-A01-C01	FL8 Factory Installed.....	\$5,829

FEL Specs

	<u>FL7</u>	<u>FL8</u>
Maximum Lift Height to Bucket Pivot Pin.....	95"	100"
Clearance with Level Bucket at Maximum Lift Height.....	86"	91"
Clearance with Bucket Dumped at Maximum Lift Height.....	72"	75"
Length with Front End Loader & 3 Pt Hitch.....	157.5"	162.3"
Reach at Maximum Lift Height.....	7"	5"
Bucket Dump Angle at Maximum Lift Height.....	50 degrees	52 degrees
Maximum Rollback Angle.....	36 degrees	32 degrees
Lift Capacity to Maximum Height at Bucket Pivot Pins.....	1369 lbs.	1389 lbs.
Loader Weight.....	915 lbs	1070 lbs
Breakout Force at Pivot Pin.....	2575 lbs	3285 lbs
Standard Bucket Width.....	60"	60"
Reach with Bucket on the Ground.....	59"	63"

CT2025/CT2035/CT2040

Compact Tractor

Part Number	Description	Dealer Installed Accessories - Order From Parts	SLP in US \$
-------------	-------------	---	--------------

For current Dealer Installed Accessories pricing, reference BobQuote or Dealer Parts Department.

Cab Accessories			
7378602	Field Cab Kit.....	\$ _____	
	Includes cab, turn signals, taillights, sound insulation, cab supports and hardware.		
	Install time: 5.0 hrs.		
7387222	Interior Material Kit.....	\$ _____	
	Field Cab required. Noise dampening material.		
7457501A	Bluetooth Radio Kit.....	\$ _____	
	Field cab required. Includes stereo, antenna and hardware. Install time: 1.0 hrs.		
7370408	Rear Wiper Kit.....	\$ _____	
	Field cab required. Includes motor, wiper arm, wiper, switch and hardware. Install time: 2.0 hrs.		
7405530	Beacon Kit for Field Cab.....	\$ _____	
	Field cab required. Includes switch, wiring, hardware, beacon lamp and bracket. Install time: 1.0 hrs.		

Hydraulic / Hitch Accessories			
7378616	4 Port Remote Hydraulic Valve (Spring).....	\$ _____	
	Includes valve, levers, couplers tubing and hardware. Install time: 1.5 hrs.		
7378619	4 Port Remote Hydraulic Valve (Detent/Spring).....	\$ _____	
	Includes valve, levers, couplers tubing and hardware. Install time: 1.5 hrs.		
7378620	4 Port Remote Hydraulic Valve (Detent).....	\$ _____	
	Includes valve, levers, couplers tubing and hardware. Install time: 1.5 hrs.		
7378636	Telescopic Lower Link Bar.....	\$ _____	
	Left and right lower link assembly. Install time: 0.25 hrs.		
7378645	Lift Rod Kit (Bevel Gear Type).....	\$ _____	
	Lift rod assembly (beveled gear type). Install time: 0.1 hrs.		

Ballast			
7402084	Front Weight Bracket (Not compatible with grille guard or FEL).....	\$ _____	
	Includes weight bracket and associated hardware. Install time: 0.5 hrs.		
7158255	Suitcase Weights - 50 lbs (22.8 kg)	\$ _____	
	Includes cast weight only. CT20xx/25xx can hold up to 6 weights. Bracket required.		

Cold Weather Accessories			
7388933	Block Heater.....	\$ _____	
	Includes block heater and instructions. Install time: 1.0 hrs.		
7401548	(FRV) Fuel Recirculation Valve Kit (Not applicable for CT2025).....	\$ _____	
	Includes valve, hoses and clamps. Install time: 1.0 hrs.		

ROPS Accessories			
7378626	Canopy.....	\$ _____	
	Includes canopy and hardware. Install time 1 hrs.		
7378634	Rear View Mirror.....	\$ _____	
	Includes mirror, bracket and hardware. Install time: 0.25 hrs.		
7E+06	Rear Working Light Kit.....	\$ _____	
	Includes light, bracket and hardware. Install time: 0.25 hrs.		

CT2025/CT2035/CT2040**Compact Tractor****Tire/Wheel Assemblies****Bias Ply Ag (R1)**

7464567	7-16 6PR R-1, Front Left	\$ _____
7464566	7-16 6PR R-1, Front Right.....	\$ _____
46932171	11.2-24 6PR R-1, Rear Left.....	\$ _____
46932172	11.2-24 6PR R-1, Rear Right.....	\$ _____

Bias Ply Industrial/General Purpose (R4)

46932154	27x8.5-15 6PR R-4, Front Left.....	\$ _____
46932153	27x8.5-15 6PR R-4, Front Right.....	\$ _____
46932159	15-19.5 6PR R-4, Rear Left.....	\$ _____
46932165	15-19.5 6PR R-4, Rear Right.....	\$ _____

Bias Ply Industrial/Ag Hybrid (R14)

46985448	27x8.5-15 6PR R-4, Front Left.....	\$ _____
46985449	27x8.5-15 6PR R-4, Front Right.....	\$ _____
46985450	15-19.5 6PR R-4, Rear Left.....	\$ _____
46985452	15-19.5 6PR R-4, Rear Right.....	\$ _____

Bias Ply Turf (R3)

46932155	27x8.50-15 6PR R-3, Front.....	\$ _____
7464572	41x14-20 4PR R-3, Rear.....	\$ _____

Front-End Loader Accessories

7393036	Bolt-on 60" Cutting Edge for FL7/FL8 (CT20xx).....	\$ _____
7392994	3rd Function Kit for FL7/FL8 (CT20xx).....	\$ _____
Includes flat face couplers (Pioneer couplers need to be ordered separately). Install time: 2.0 hrs.		

Additional Accessories

7378612	Mid PTO Kit.....	\$ _____
Includes PTO, lever and hardware. Install time: 1.5 hrs.		
7378640	HST Cruise Kit (HST Only).....	\$ _____
Includes relay, switch, harness, cruise magnet and hardware. Install time: 0.75 hrs.		
7378650	HST Linked Pedal Kit (HST Only).....	\$ _____
Complete linked pedal assembly. Install time: 2.0 hrs.		
7378628	Clevis Drawbar Kit.....	\$ _____
Drawbar assembly. Install time: 0.25 hrs.		
7E+06	Toolbox.....	\$ _____
Includes tool box, brackets and hardware. Install time: 0.25 hrs.		
7378637	Dual Air Filter Kit.....	\$ _____
Filter element. Install time: 0.1 hrs.		
7378647	Right Armrest Kit.....	\$ _____
Seat armrest assembly. Install time: 0.1 hrs.		
7388810	Spark Arrestor Muffler Kit (CT2025 MST and HST only).....	\$ _____
Includes spark arrestor and hardware. Install time: 0.25 hrs.		
7392252	Translation Kit.....	\$ _____
Includes decals, Operator's Handbook, Safety Manual and Warranty Brochure. Install time: 0.25 hrs		

CT2535/CT2540

Compact Tractor



Standard Equipment

Brakes, Wet Multi Disc

Cab – Heat/Air

Cruise Control

Cupholder

Draw Bar, Adjustable

Dual Air Cleaner

Dual Arm Rest

Dual Remote Valves (4 port)

Electric Key Shutoff

Floor-mat

Four Wheel Drive

Front Work light

Fuel Heater Kit

Glow Plug Engine Pre-Heat

Horn

Hydraulic Three-Point Lift Position Control System

Hydraulic Power Steering, Tilt Steering

Instrumentation: Hourmeter, Tachometer, Engine

- Temperature, Fuel Gauge, and Warning Lights

Lift rod – Beveled gear type

Lights: Headlights, Tail Lights, Brake Lights, Hazard
- Flashers, and Turn Signals

Loader Joystick & Valve

Parking Brake

PTO Shield

Rear Differential Lock

Rear PTO (Independent)

Rear Three-Point Hitch Return to Position

Rear View Mirror

Rear Window Wiper/Defrost

Rear Work Light

Safety Interlock System

Side View Mirror

Sun-visor

Telescopic Stabilizer & Lower Link

Three-Point Hitch, Category I

Tires: Industrial 27X8.5-15, Front; 15-19, Rear

Tool Box

Vinyl Suspension Seat, w/ Retractable Seat Belt

****The CT25xx platform comes standard with 2 pair (4 ports) of rear remote hydraulics****

* Roll Over Protective Structure (ROPS) - Meets Requirements of ISO12003-2.

CT2535/CT2540**Compact Tractor****Quick Specs**

	<u>CT2535 HST</u>	<u>CT2540 HST</u>
Engine - Tier IV Compliant.....	3H-TH4B	3H-TH4B
Engine Fuel/Cooling.....	Diesel/Liquid	Diesel/Liquid
Gross Horsepower.....	34.9 hp	37.6 hp
Engine Displacement.....	111.4 cu. in.	111.4 cu. in.
PTO Horsepower.....	29.4 hp	31.9 hp
PTO RPM.....	540	540
Alternator Capacity.....	75 amps	75 amps
Travel Speed (Forward) w/ R-4 Ind Tires.....	14 mph	14 mph
Travel Speed (Reverse) w/ R-4 Ind Tires.....	9.7 mph	9.7 mph
Operating Weight.....	3585 lbs.	3585 lbs.
Height - Top of Structure w/ R-4 Ind Tires.....	91.0 in.	91.0 in.
Transmission.....	Hydrostatic	Hydrostatic
Width w/ R-4 Ind Tires.....	63.0 in.	63.0 in.
Width w/ Ag Tires.....	59.6 in.	59.6 in.
Width w/Turf Tires.....	63.7 in.	63.7 in.
Length w/ 3 Pt. Hitch (no weight bracket).....	120.9 in.	120.9 in.
Length with Front End Loader & 3 Pt Hitch.....	162.3 in.	162.3 in.
Wheelbase.....	65.7 in.	65.7 in.
Min. Ground Clearance w/ R-4 Ind Tires.....	12.3 in.	12.3 in.
Inside Turning Radius.....	106.3 in.	106.3 in.
Fuel Tank Capacity.....	9.0 gal.	9.0 gal.
3Pt Hitch Lift Cap (24" behind lift point with FEL).....	1631 lbs. *	1631 lbs. *
Hydraulic Pump Flow.....	11.4 gpm	11.4 gpm
Implement Flow.....	6.9 gpm	6.9 gpm
Steering Flow.....	4.5 gpm	4.5 gpm

* With front end loader installed (used as front ballast)

CT2535/CT2540**Compact Tractor****Ordering Path:**

- 1) Select Tractor Model
- 2) Select Tire (Pricing dependent on option)
- 3) Select Factory Installed Front End Loader (Optional)

Part Number	Description	Compact Utility Tractor	SLP in US \$
-------------	-------------	-------------------------	--------------

M1609	CT2535HST Compact Tractor.....		\$41,173
M1611	CT2540HST Compact Tractor.....		\$43,263

Part Number	Description	Factory Installed Options	SLP in US \$
-------------	-------------	---------------------------	--------------

Tire Options

M_-R02-C01	Ag Tire: 7-16 8PR, Front; 11.2-24 6PR, Rear.....	\$395
	<i>Superior traction in muddy & soft soil, ideal for maximum pulling power & maneuverability in rugged conditions.</i>	
M_-R02-C02	Ind Tire (Standard): 27x8.5-15 6PR, Front; 15-19.5 6PR, Rear.....	\$263
	<i>Balanced combination of traction & surface area. Ideal for optimizing traction & minimizing ground disturbance.</i>	
M_-R02-C03	Turf Tire: 27x8.5-15 6PR, Front; 41x14-20 4PR, Rear.....	\$395
	<i>Maximizes surface area for minimal ground disturbance, ideal for protecting lawn/grass & icy conditions.</i>	
M_-R02-C07	Ind/Ag Hybrid Tire: 27x8.5-15 6PR, Front; 15-19.5 6PR, Rear.....	\$592
	<i>Premium, hybrid tread which combines traction of ag tire with high surface area & ride quality of the industrial tire.</i>	

Front End Loader - Bob-Tach

Includes quick attach front-end loader, hose kit, bucket level indicator, grille guard, mounting kit, joystick valve and 60" Bob-Tach bucket. (For maximum lift capacity, equip with rear ballast box)

M_-A01-C01	FL8 Factory Installed.....	\$5,829
------------	----------------------------	---------

FEL Specs

	FL8
Maximum Lift Height to Bucket Pivot Pin.....	100"
Clearance with Level Bucket at Maximum Lift Height.....	91"
Clearance with Bucket Dumped at Maximum Lift Height.....	75"
Reach at Maximum Lift Height.....	5"
Length with Front End Loader & 3 Pt Hitch.....	162.3"
Bucket Dump Angle at Maximum Lift Height.....	52 degrees
Maximum Rollback Angle.....	32 degrees
Lift Capacity to Maximum Height at Bucket Pivot Pins.....	1389 lbs.
Loader Weight.....	1070 lbs
Breakout Force at Pivot Pin.....	3285 lbs
Standard Bucket Width.....	60"
Reach with Bucket on the Ground.....	63"

CT2535/CT2540**Compact Tractor**

Part Number	Description	Dealer Installed Accessories - Order From Parts	SLP in US \$
-------------	-------------	---	--------------

For current Dealer Installed Accessories pricing, reference BobQuote or Dealer Parts Department.

Cab Accessories			
7457509A	Bluetooth Radio Kit.....	\$ _____	
	Includes stereo, harness and hardware. Install time: 1.0 hrs.		
7384214	Beacon Kit.....	\$ _____	
	Includes lamp switch, wiring, hardware, beacon lamp and bracket. Install time: 1.0 hr.		

Hydraulic / Hitch Accessories			
7384208	Detent Kit.....	\$ _____	
	Detent support plate assembly		

Ballast			
7402084	Front Weight Bracket (Not compatible with grille guard or FEL).....	\$ _____	
	Includes weight bracket and associated hardware. Install time: 0.5 hrs.		
7158255	Suitcase Weights - 50 lbs (22.8 kg)	\$ _____	
	Includes cast weight only. CT20xx/25xx can hold up to 6 weights. Bracket required.		

Cold Weather			
7401548	(FRV) Fuel Recirculation Valve Kit.....	\$ _____	
	Includes valve, hoses and clamps. Install time: 1.0 hrs.		
7388933	Block Heater.....	\$ _____	
	Includes block heater and instructions. Install time: 1.0 hrs.		

Tire/Wheel Assemblies			
Bias Ply Ag (R1)			
7464567	7-16 6PR R-1, Front Left	\$ _____	
7464566	7-16 6PR R-1, Front Right.....	\$ _____	
7464565	11.2-24 6PR R-1, Rear Left.....	\$ _____	
7464564	11.2-24 6PR R-1, Rear Right.....	\$ _____	
Bias Ply Industrial/General Purpose (R4)			
46884900	27x8.5-15 6PR R-4, Front Left.....	\$ _____	
46884899	27x8.5-15 6PR R-4, Front Right.....	\$ _____	
7464569	15-19.5 6PR R-4, Rear Left.....	\$ _____	
7464568	15-19.5 6PR R-4, Rear Right.....	\$ _____	
Bias Ply Industrial/Ag Hybrid (R14)			
46985448	27x8.5-15 6PR R-4, Front Left.....	\$ _____	
46985449	27x8.5-15 6PR R-4, Front Right.....	\$ _____	
46985450	15-19.5 6PR R-4, Rear Left.....	\$ _____	
46985452	15-19.5 6PR R-4, Rear Right.....	\$ _____	
Bias Ply Turf (R3)			
46884901	27x8.50-15 6PR R-3, Front.....	\$ _____	
7464572	41x14-20 4PR R-3, Rear.....	\$ _____	

Front-End Loader Accessories			
7393036	Bolt-on 60" Cutting Edge for FL8 (CT25xx).....	\$ _____	
7392994	3rd Function Kit for FL8 (CT25xx).....	\$ _____	
	Includes flat face couplers (Pioneer couplers need to be ordered separately). Install time: 2.0 hrs.		

Additional Accessories			
7384209	Mid PTO Kit.....	\$ _____	
	Includes PTO, lever and hardware. Install time: 1.5 hr.		
7378628	Clevis Drawbar Kit.....	\$ _____	
	Drawbar assembly. Install time: 0.25 hr.		
7392577	Translation Kit.....	\$ _____	
	Includes decals, Operator's Handbook, Safety Manual and Warranty Brochure. Install time: 0.25 hrs		

CT4045/CT4050/CT4055/CT4058

Compact Tractor



Standard Equipment

Brakes, Wet Multi Disc	Lights: Headlights, Tail Lights, Brake Lights, Hazard
Cupholder	- Flashers, and Turn Signals
Draw Bar, Adjustable	Parking Brake
Electric Key Shutoff	PTO Shield
Floor Mat	Rear Differential Lock
Four Wheel Drive	Rear PTO (Independent)
Fuel Heater	Rear Three-Point Hitch Return to Position
Glow Plug Engine Pre-Heat	ROPS – two-post, Foldable *
Horn	Safety Interlock System
Hydraulic Three-Point Lift Position Control System	Three-Point Hitch, Category 1
Hydraulic Power Steering	Std. Tires (Industrial):
Instrumentation: Hourmeter, Tachometer, Engine	- 10-16.5 – Front; 17.5-24 – Rear
- Temperature, Fuel Gauge, and Warning Lights	Toolbox
Lift rod – Turnbuckle	Vinyl Suspension Seat, w/ Retractable Seat Belt

****The HST models of the CT40xx platform come standard with 1 pair (2 ports) of detent rear remote hydraulics. The SST come with zero standard.****

* Roll Over Protective Structure (ROPS) - Meets Requirements of OECD Code 4 and Field Cab Option meets EEC 79/622

Quick Specs

	CT4045 HST	CT4045 SST	CT4050 HST	CT4050 SST	CT4055 SST	CT4058 HST
		<i>Discontinued</i>	<i>Discontinued</i>		<i>Discontinued</i>	
Engine - Tier IV Compliant.....	3HT-TH4C	3HT-TM4B	3HT-TH4C	3HT-TM4B	3HT-TM4B	3HT-TH4C
Engine Fuel/Cooling.....	Diesel/Liquid	Diesel/Liquid	Diesel/Liquid	Diesel/Liquid	Diesel/Liquid	Diesel/Liquid
Gross Horsepower.....	44.9 hp	44.9 hp	50.3 hp	50.3 hp	55 hp	57.7 hp
Engine Displacement.....	111.4 cu. in.	111.4 cu. in.	111.4 cu. in.	111.4 cu. in.	111.4 cu. in.	111.4 cu. in.
PTO Horsepower.....	32.8 hp	41.6 hp	39.3 hp	45.6 hp	49.6 hp	45.1 hp
PTO RPM.....	540	540	540	540	540	540
Alternator Capacity.....	75 amps	75 amps	75 amps	75 amps	75 amps	75 amps
Travel Speed (Forward) w/ R-4 Ind Tires.....	18 mph	16.3 mph	18 mph	16.3 mph	16.3 mph	18 mph
Travel Speed (Reverse) w/ R-4 Ind Tires.....	12.6 mph	15.9 mph	12.6 mph	15.9 mph	15.9 mph	12.6 mph
Operating Weight.....	3745 lbs.	3745 lbs.	3745 lbs.	3745 lbs.	3745 lbs.	3745 lbs.
Height - Top of Structure w/ R-4 Ind Tires.....	97.4 in.	97.4 in.	97.4 in.	97.4 in.	97.4 in.	97.4 in.
Width w/ R-4 Ind Tires.....	70.3 in.	70.3 in.	70.3 in.	70.3 in.	70.3 in.	70.3 in.
Width w/ Ag Tires.....	62.8 in.	62.8 in.	62.8 in.	62.8 in.	62.8 in.	62.8 in.
Width w/Turf Tires.....	70.3 in.	70.3 in.	70.3 in.	70.3 in.	70.3 in.	70.3 in.
Length w/ 3 Pt. Hitch (no weight bracket).....	125.5 in.	125.5 in.	125.5 in.	125.5 in.	125.5 in.	125.5 in.
Wheelbase.....	71.2 in.	71.2 in.	71.2 in.	71.2 in.	71.2 in.	71.2 in.
Min. Ground Clearance w/ R-4 Ind Tires.....	15.3 in.	15.3 in.	15.3 in.	15.3 in.	15.3 in.	15.3 in.
Inside Turning Radius.....	103.5 in.	103.5 in.	103.5 in.	103.5 in.	103.5 in.	116.1 in.
Fuel Tank Capacity.....	12.7 gal.	11.9 gal.	12.7 gal.	11.9 gal.	11.9 gal.	12.7 gal.
3Pt Hitch Lift Cap (24" behind lift point with FEL).	2716 lbs. *	2716 lbs. *	2716 lbs. *	2716 lbs. *	2716 lbs. *	2716 lbs. *
Hydraulic Pump Flow.....	16.5 gpm	14.1 gpm	16.5 gpm	16.5 gpm	14.1 gpm	16.5 gpm
Implement Flow.....	9.6 gpm	9.6 gpm	9.6 gpm	9.6 gpm	9.6 gpm	9.6 gpm
Steering Flow.....	6.9 gpm	4.5 gpm	6.9 gpm	4.5 gpm	4.5 gpm	6.9 gpm

CT4045/CT4050/CT4055/CT4058

Compact Tractor

Ordering Path:

- 1) Select Tractor Model
- 2) Select Tire (Pricing dependent on option)
- 3) Select Factory Installed Front End Loader (Optional)

Part Number	Description	Compact Utility Tractor	SLP in US \$
M1636	CT4045HST Compact Tractor.....		\$34,400
M1634	CT4045SST Compact Tractor (Discontinued).....		\$30,993
M1637	CT4050HST Compact Tractor (Discontinued).....		\$38,479
M1625	CT4050SST Compact Tractor.....		\$32,608
M1635	CT4055SST Compact Tractor (Discontinued).....		\$34,224
M1638	CT4058HST Compact Tractor.....		\$41,048

Part Number	Description	Factory Installed Options	SLP in US \$
-------------	-------------	---------------------------	--------------

Tire Options

M_-R02-C01	Ag Tire: 8-16 6PR Front; 13.6-24 8PR Rear.....	\$789
	<i>Superior traction in muddy & soft soil, ideal for maximum pulling power & maneuverability in rugged conditions.</i>	
M_-R02-C02	Ind Tire (Standard): 10-16.5 6PR Front; 17.5-24 6PR Rear.....	\$592
	<i>Balanced combination of traction & surface area. Ideal for optimizing traction & minimizing ground disturbance.</i>	
M_-R02-C03	Turf Tire: 10-16.5 8PR Front; 17.5-24 8PR Rear.....	\$789
	<i>Maximizes surface area for minimal ground disturbance, ideal for protecting lawn/grass & icy conditions.</i>	
M_-R02-C07	Ind/Ag Hybrid Tire: 10-16.5 6PR Front; 17.5-24 6PR Rear.....	\$987
	<i>Premium, hybrid tread which combines traction of ag tire with high surface area & ride quality of the industrial tire.</i>	

Front End Loader - Bob-Tach

Includes quick attach front-end loader, hose kit, bucket level indicator, grille guard, mounting kit, joystick valve and 66" Bob-Tach bucket. (For maximum lift capacity, equip with rear ballast box)

M_-A01-C01 FL9 Factory Installed..... \$7,839

FEL Specs

	<u>FL9</u>
Maximum Lift Height to Bucket Pivot Pin.....	103"
Clearance with Level Bucket at Maximum Lift Height.....	92"
Clearance with Bucket Dumped at Maximum Lift Height.....	75"
Reach at Maximum Lift Height.....	11"
Length with Front End Loader & 3 Pt Hitch.....	176"
Bucket Dump Angle at Maximum Lift Height.....	51 degrees
Maximum Rollback Angle.....	36 degrees
Lift Capacity to Maximum Height at Bucket Pivot Pins.....	1795 lbs
Loader Weight.....	1202 lbs
Breakout Force at Pivot Pin.....	3938 lbs
Standard Bucket Width.....	66"
Reach with Bucket on the Ground.....	69"

CT4045/CT4050/CT4055/CT4058

Compact Tractor

Part Number	Description	Dealer Installed Accessories - Order From Parts	SLP in US \$
-------------	-------------	---	--------------

For current Dealer Installed Accessories pricing, reference BobQuote or Dealer Parts Department.

Hydraulic / Hitch Accessories			
7384219	Single Rear Remote Hydraulic (Spring).....	\$ _____	
	Includes valve couplers, levers and hardware. Install time: 1.5 hrs.		
7384220	Single Rear Remote Hydraulic (Detent) (Standard on HST models).....	\$ _____	
	Includes valve couplers, levers and hardware. Install time: 1.5 hrs.		
7384221	Second Rear Remote Hydraulic (Spring).....	\$ _____	
	Includes valve double acting couplers, levers and hardware. Install time: 1.5 hrs.		
7384222	Second Remote Hydraulic (Detent).....	\$ _____	
	Includes valve double acting couplers, levers and hardware. Install time: 1.5 hrs.		
7378628	Clevis Drawbar Kit.....	\$ _____	
	Drawbar assembly. Install time: 0.25 hrs.		
7384230	Quick Type Link Kit.....	\$ _____	
	Left and right lower link assembly		
7387328	Telescopic Lower Link Bar.....	\$ _____	
	Left and right lower link assembly. Install time: 0.25 hrs.		

Ballast			
7402084	Front Weight Bracket (Not compatible with grille guard or FEL).....	\$ _____	
	Includes weight bracket and associated hardware. Install time: 0.5 hrs.		
7158255	Suitcase Weights - 50 lbs (22.8 kg)	\$ _____	
	Includes cast weight only. CT40xx can hold up to 6 weights. Bracket required.		

Cold Weather			
7401548	(FRV) Fuel Recirculation Valve Kit.....	\$ _____	
	Includes valve, hoses and clamps. Install time: 1.0 hrs.		
7388933	Block Heater.....	\$ _____	
	Includes block heater and instructions. Install time: 1.0 hrs.		

ROPS Accessories			
7384223	Rear Working Light.....	\$ _____	
	Includes light, bracket and hardware. Install time: 0.25 hrs.		
7384228	Rear View Mirror.....	\$ _____	
	Includes mirror, bracket and hardware. Install time: 0.25 hrs.		
7378626	Canopy.....	\$ _____	
	Includes canopy and hardware. Install time 1 hrs.		
7384233	Front Working Light Kit.....	\$ _____	
	Includes left and right light assemblies, switch, relay and hardware. Install time: 1.5 hrs.		

Tire/Wheel Assemblies**Bias Ply Ag (R1)**

7464585	8-16 6PR R-1, Front Left	\$ _____
7464584	8-16 6PR R-1, Front Right.....	\$ _____
46932167	13.6-24 8PR R-1, Rear Left.....	\$ _____
46932166	13.6-24 8PR R-1, Rear Right.....	\$ _____

Bias Ply Industrial/General Purpose (R4)

46932170	10-16.5 6PR R-4, Front Left.....	\$ _____
46932169	10-16.5 6PR R-4, Front Right.....	\$ _____
46932156	17.5-24 6PR R-4, Rear Left.....	\$ _____
46932157	17.5-24 6PR R-4, Rear Right.....	\$ _____

Bias Ply Industrial/Ag Hybrid (R14)

46985456	10-16.5 6PR R-4, Front Left.....	\$ _____
46985457	10-16.5 6PR R-4, Front Right.....	\$ _____
46985458	17.5-24 6PR R-4, Rear Left.....	\$ _____
46985455	17.5-24 6PR R-4, Rear Right.....	\$ _____

Bias Ply Turf (R3)

46932168	10-16.5 8PR R-3, Front.....	\$ _____
46932158	17.5L-24 8PR R-3, Rear.....	\$ _____

Front-End Loader Accessories

7393039	Bolt-on 66" Cutting Edge for FL9 (CT40xx).....	\$ _____
7392997	3rd Function Kit for FL9 (CT40xx).....	\$ _____

Includes flat face couplers (Pioneer couplers need to be ordered separately). Install time: 2.0 hrs.

Additional Accessories

7384235	Mid PTO Kit (HST Only)(Not compatible with BH86 backhoe).....	\$ _____
Includes Mid PTO, PTO lever and hardware. Install time: 1.5 hrs.		
7387332	Cruise Control (HST Models Only).....	\$ _____
Includes cruise magnet, switch, relay and associated hardware. Install time: 1.0 hrs.		
7387331	HST Linked Pedal Kit (HST Only).....	\$ _____
Complete linked pedal assembly. Install time: 2.0 hrs.		
7387333	Dual Armrest Kit (HST Only).....	\$ _____
Includes right and left armrests and related hardware. Install time: 0.25 hrs.		
7E+06	Power Socket Kit.....	\$ _____
Includes power socket and wire harness. Install time: 0.25 hrs.		
7384225	3-Pin Socket.....	\$ _____
Includes 3-pin socket, wire and connectors and hardware. Install time: 0.25 hrs.		
7384234	Jump Start Kit (SST only).....	\$ _____
Includes jump start assembly and hardware. Install time: 0.25 hrs.		
7393118	Translation Kit.....	\$ _____
Includes decals, Operator's Handbook, Safety Manual, and Warranty Brochure. Install time: 0.25 hrs		

Field Cab & Accessories

7384217	Field Cab Kit - SST Models Only.....	\$ _____
Includes cab, turn signals, taillights, sound insulation, cab supports and hardware. Install time: 5.0 hrs.		
7370408	Rear Wiper Kit.....	\$ _____
Field cab required. Includes motor, wiper arm, wiper, switch and hardware. Install time: 2.0 hrs.		
7370409	Beacon Light Kit.....	\$ _____
Field cab required. Includes switch, wiring, hardware, beacon lamp and bracket. Install time: 1.0 hrs.		
7387330	Interior Material Kit.....	\$ _____
Field cab required. Noise dampening material.		
7457501A	Bluetooth Radio Kit.....	\$ _____
Field cab required. Includes stereo, antenna and hardware. Install time: 1.0 hrs.		

CT4545/CT4558

Compact Tractor



Standard Equipment

7-pin Socket	Loader Joystick & Valve
Brakes, Wet Multi Disc	Parking Brake
Cab – Heat/Air	PTO Cruise
Cupholder	PTO Shield
Electric Key Shutoff	Rear Differential Lock
Floor Mat	Rear PTO (Independent)
Four Wheel Drive	Rear Three-Point Hitch Return to Position
Fuel Heater	Right Arm Rest
Glow Plug Engine Pre-Heat	Safety Interlock System
Horn	Side View Mirrors
Hydraulic Three-Point Lift Position Control System	Three-Point Hitch, Category 1
Hydraulic Power Steering	Tires: Industrial 10–16.5 – Front; 17.5-24 – Rear
Instrumentation: Hourmeter, Tachometer, Engine - Temperature, Fuel Gauge, and Warning Lights	Tool Box
Lifting Rod – Beveled Gear Type	Vinyl Suspension Seat, w/ Retractable Seat Belt
Lights: Headlights, Tail Lights, Brake Lights, Hazard - Flashers, and Turn Signals	

****The CT45xx platform comes standard with 1 pair (2 ports) of spring rear remote hydraulics****

* Roll Over Protective Structure (ROPS) - Meets Requirements of OECD Code 4

CT4545/CT4558 Compact Tractor
--

Quick Specs

	<u>CT4545 HST</u>	<u>CT4558 HST</u>
Engine - Tier IV Compliant.....	3HT-TM4B	3HT-TM4B
Engine Fuel/Cooling.....	Diesel/Liquid	Diesel/Liquid
Gross Horsepower.....	44.9 HP	57.7 HP
Engine Displacement.....	111.4 cu. in.	111.4 cu. in.
PTO Horsepower.....	32.8 HP	45.1 HP
PTO RPM.....	540	540
Alternator Capacity.....	75 amps	75 amps
Travel Speed (Forward) w/ R-4 Ind Tires.....	16.3 mph	18.0 mph
Travel Speed (Reverse) w/ R-4 Ind Tires.....	15.9 mph	12.6 mph
Operating Weight.....	4300 lbs.	4300 lbs.
Height - Top of Structure w/ R-4 Ind Tires.....	94.3 in.	94.3 in.
Transmission.....	Hydrostatic	Hydrostatic
Width w/ R-4 Ind Tires.....	70.3 in.	70.3 in.
Width w/ Ag Tires.....	62.8 in.	62.8 in.
Width w/Turf Tires.....	70.3 in.	70.3 in.
Length w/ 3 Pt. Hitch (no weight bracket).....	125.5 in.	125.5 in.
Wheelbase.....	71.2 in.	71.2 in.
Min. Ground Clearance w/ R-4 Ind Tires.....	15.3 in.	15.3 in.
Inside Turning Radius.....	116.1 in.	116.1 in.
Fuel Tank Capacity.....	11.9 gal.	11.9 gal.
3Pt Hitch Lift Cap (24" behind lift point with FEL).	2716 lbs. *	2716 lbs. *
Hydraulic Pump Flow.....	16.5 gpm	16.5 gpm
Implement Flow.....	9.6 gpm	9.6 gpm
Steering Flow.....	6.9 gpm	6.9 gpm

* With front end loader installed (used as front ballast)

CT4545/CT4558 Compact Tractor

Ordering Path:

- 1) Select Tractor Model
- 2) Select Tire (Pricing dependent on option)
- 3) Select Factory Installed Front End Loader (Optional)

Part Number	Description	Compact Utility Tractor	SLP in US \$
-------------	-------------	-------------------------	--------------

M1639	CT4545HST Compact Tractor.....		\$45,414
M1641	CT4558HST Compact Tractor.....		\$49,846

Part Number	Description	Factory Installed Options	SLP in US \$
-------------	-------------	---------------------------	--------------

Tire Options

M_-R02-C01	Ag Tire: 8-16 6PR Front; 13.6-24 8PR Rear.....	\$789
	<i>Superior traction in muddy & soft soil, ideal for maximum pulling power & maneuverability in rugged conditions.</i>	
M_-R02-C02	Ind Tire (Standard): 10-16.5 6PR Front; 17.5-24 6PR Rear.....	\$592
	<i>Balanced combination of traction & surface area. Ideal for optimizing traction & minimizing ground disturbance.</i>	
M_-R02-C03	Turf Tire: 10-16.5 8PR Front; 17.5-24 8PR Rear.....	\$789
	<i>Maximizes surface area for minimal ground disturbance, ideal for protecting lawn/grass & icy conditions.</i>	
M_-R02-C07	Ind/Ag Hybrid Tire: 10-16.5 6PR Front; 17.5-24 6PR Rear.....	\$987
	<i>Premium, hybrid tread which combines traction of ag tire with high surface area & ride quality of the industrial tire.</i>	

Front End Loader - Bob-Tach

Includes quick attach front-end loader, hose kit, bucket level indicator, grille guard, mounting kit, and 66" Bob-Tach bucket. (For maximum lift capacity, equip with rear ballast box)

M_-R01-C01	FL9-2 Factory Installed.....	\$7,839
------------	------------------------------	---------

FEL Specs

	FL9-2
Maximum Lift Height to Bucket Pivot Pin.....	103"
Clearance with Level Bucket at Maximum Lift Height.....	92"
Clearance with Bucket Dumped at Maximum Lift Height.....	75"
Reach at Maximum Lift Height.....	28"
Length with Front End Loader & 3 Pt Hitch.....	176"
Bucket Dump Angle at Maximum Lift Height.....	51 degrees
Maximum Rollback Angle.....	36 degrees

Lift Capacity to Maximum Height at Bucket Pivot Pins.....	1795 lbs
Loader Weight.....	1050 lbs
Breakout Force at Pivot Pin.....	3938 lbs
Standard Bucket Width.....	66"
Reach with Bucket on the Ground.....	69"

CT4545/CT4558**Compact Tractor**

Part Number	Description	Dealer Installed Accessories - Order From Parts	SLP in US \$
-------------	-------------	---	--------------

For current Dealer Installed Accessories pricing, reference BobQuote or Dealer Parts Department.

Cab Accessories			
46950493	Rear Wiper Kit.....	\$ _____	
	Includes motor, wiper arm, wiper, switch and hardware. Install time: 2.0 hrs.		
46950487	Beacon Kit.....	\$ _____	
	Includes lamp switch, wiring, hardware, beacon lamp and bracket. Install time: 1.0 hrs.		
7457509A	Bluetooth Radio Kit.....	\$ _____	
	Includes radio, harness and hardware. Install time: 1.0 hrs.		

Hydraulic / Hitch Accessories			
7384221	Second Rear Remote Valve (Spring).....	\$ _____	
	Includes second valve body, lever, cable and associated hardware. Install time: 1.5 hrs.		
7384222	Second Rear Remote Valve (Detent).....	\$ _____	
	Includes second valve body, lever, cable and associated hardware. Install time: 1.5 hrs.		
7389294A	Telescopic Lower Link Bar.....	\$ _____	
	Left and right lower link assembly. Install time: 0.25 hrs.		

Ballast			
7402084	Front Weight Bracket (Not compatible with grille guard or FEL).....	\$ _____	
	Includes weight bracket and associated hardware. Install time: 0.5 hrs.		
7158255	Suitcase Weights - 50 lbs (22.8 kg)	\$ _____	
	Includes cast weight only. CT55xx can hold up to 6 weights. Bracket required.		

Cold Weather Accessories			
7401548	(FRV) Fuel Recirculation Valve Kit.....	\$ _____	
	Includes valve, hoses, and clamps. Install time: 1.0 hrs.		
7388933	Block Heater.....	\$ _____	
	Includes block heater and instructions. Install time: 1.0 hrs.		

Tire/Wheel Assemblies			
Bias Ply Ag (R1)			
7464585	8-16 6PR R-1, Front Left	\$ _____	
7464584	8-16 6PR R-1, Front Right.....	\$ _____	
46932167	13.6-24 8PR R-1, Rear Left.....	\$ _____	
46932166	13.6-24 8PR R-1, Rear Right.....	\$ _____	
Bias Ply Industrial/General Purpose (R4)			
46932170	10-16.5 6PR R-4, Front Left.....	\$ _____	
46932169	10-16.5 6PR R-4, Front Right.....	\$ _____	
46932156	17.5-24 6PR R-4, Rear Left.....	\$ _____	
46932157	17.5-24 6PR R-4, Rear Right.....	\$ _____	
Bias Ply Industrial/Ag Hybrid (R14)			
46985456	10-16.5 6PR R-4, Front Left.....	\$ _____	
46985457	10-16.5 6PR R-4, Front Right.....	\$ _____	
46985458	17.5-24 6PR R-4, Rear Left.....	\$ _____	
46985455	17.5-24 6PR R-4, Rear Right.....	\$ _____	
Bias Ply Turf (R3)			
46932168	10-6.5 8PR R-3, Front.....	\$ _____	
46932158	17.5L-24 8PR R-3, Rear.....	\$ _____	

Front-End Loader Accessories			
7393039	Bolt-on 66" Cutting Edge for FL9-2 (CT45xx).....	\$ _____	
46950497	3rd Function Kit for FL9-2 (CT45xx).....	\$ _____	
	Includes flat face couplers (Pioneer couplers need to be ordered separately). Install time: 2.0 hrs.		

Additional Accessories		
7384235	Mid PTO Kit.....	\$ _____
	Mid PTO assembly. Includes lever and hardware. Install time: 1.5 hrs.	
7389456A	Linked Pedal.....	\$ _____
	Complete linked pedal assembly. Install time: 2.0 hrs.	
7389457A	Cruise Control.....	\$ _____
	Includes cruise magnet, switch, relay and associated hardware. Install time: 1.0 hrs.	
7378637	Air Cleaner Inner Filter.....	\$ _____
	Filter element. Install time: 0.1 hrs.	
46955437	Translation Kit.....	\$ _____
	Includes decals, Operator's Handbook, Safety Manual, and Warranty Brochure. Install time: 0.25 hrs	

CT5545/CT5550/CT5555/CT5558

Compact Tractor



Standard Equipment

7-pin Socket	Linked Pedal
Brakes, Wet Multi Disc	Loader Joystick & Valve
Cab – Heat/Air	Parking Brake
Cruise Control	PTO Cruise
Cupholder	PTO Shield
Electric Key Shutoff	Rear Differential Lock
Floor Mat	Rear PTO (Independent)
Four Wheel Drive	Rear Three-Point Hitch Return to Position
Fuel Heater	Right Arm Rest
Glow Plug Engine Pre-Heat	Safety Interlock System
Horn	Side View Mirrors
Hydraulic Three-Point Lift Position Control System	Telescopic stabilizer and lower link
Hydraulic Power Steering	Three-Point Hitch, Category 1
Instrumentation: Hourmeter, Tachometer, Engine - Temperature, Fuel Gauge, and Warning Lights	Tires: Industrial 10–16.5 – Front; 17.5-24 – Rear
Lifting Rod – Beveled Gear Type	Cloth Suspension Seat, w/ Retractable Seat Belt
Lights: Headlights, Tail Lights, Brake Lights, Hazard - Flashers, and Turn Signals	

****The CT55xx platform comes standard with 1 pair (2 ports) of spring rear remote hydraulics****

* Roll Over Protective Structure (ROPS) - Meets Requirements of OECD Code 4

CT5545/CT5550/CT5555/CT5558 Compact Tractor
--

Quick Specs

	<u>CT5545 E-HST</u>	<u>CT5550 E-HST</u>	<u>CT5555 E-HST</u>	<u>CT5558 E-HST</u>
		<i>Discontinued</i>	<i>Discontinued</i>	
Engine - Tier IV Compliant.....	3HT-TM4B	3HT-TM4B	3HT-TH4D	3HT-TH4D
Engine Fuel/Cooling.....	Diesel/Liquid	Diesel/Liquid	Diesel/Liquid	Diesel/Liquid
Gross Horsepower.....	44.9 HP	57.7 HP	45 hp	50 hp
Engine Displacement.....	111.4 cu. in.	111.4 cu. in.	111.4 cu. in.	111.4 cu. in.
PTO Horsepower.....	32.8 HP	45.1 HP	33.9 hp	38.9 hp
PTO RPM.....	540	540	540	540
Alternator Capacity.....	75 amps	75 amps	75 amps	75 amps
Travel Speed (Forward) w/ R-4 Ind Tires.....	16.3 mph	18.0 mph	17.5 mph	17.5 mph
Travel Speed (Reverse) w/ R-4 Ind Tires.....	15.9 mph	12.6 mph	17.5 mph	17.5 mph
Operating Weight.....	4300 lbs.	4300 lbs.	4685 lbs.	4685 lbs.
Height - Top of Structure w/ R-4 Ind Tires.....	94.2 in.	94.2 in.	94.2 in.	94.2 in.
Transmission.....	Hydrostatic	Hydrostatic	E-Hydrostatic	E-Hydrostatic
Width w/ R-4 Ind Tires.....	70.3 in.	70.3 in.	74.2 in.	74.2 in.
Width w/ Ag Tires.....	62.8 in.	62.8 in.	71.2 in.	71.2 in.
Width w/Turf Tires.....	70.3 in.	70.3 in.	71.8 in.	71.8 in.
Length w/ 3 Pt. Hitch (no weight bracket).....	125.5 in.	125.5 in.	139.6 in.	139.6 in.
Wheelbase.....	71.2 in.	71.2 in.	75.6 in.	75.6 in.
Min. Ground Clearance w/ R-4 Ind Tires.....	15.3 in.	15.3 in.	13.0 in.	13.0 in.
Inside Turning Radius.....	116.1 in.	116.1 in.	117.6 in.	117.6 in.
Fuel Tank Capacity.....	11.9 gal.	11.9 gal.	14.8 gal.	14.8 gal.
3Pt Hitch Lift Cap (24" behind lift point with FEL).	2716 lbs. *	2716 lbs. *	3117 lbs. *	3177 lbs. *
Hydraulic Pump Flow.....	16.5 gpm	16.5 gpm	17.8 gpm	17.8 gpm
Implement Flow.....	9.6 gpm	9.6 gpm	9.6 gpm	9.6 gpm
Steering Flow.....	6.9 gpm	6.9 gpm	8.2 gpm	8.2 gpm

* With front end loader installed (used as front ballast)

CT5545/CT5550/CT5555/CT5558

Compact Tractor

Ordering Path:

- 1) Select Tractor Model
- 2) Select Tire (Pricing dependent on option)
- 3) Select Factory Installed Front End Loader (Optional)

Part Number	Description	Compact Utility Tractor	SLP in US \$
M1619	CT5545E-HST Compact Tractor.....		\$46,887
M1620	CT5550E-HST Compact Tractor (Discontinued).....		\$49,814
M1621	CT5555E-HST Compact Tractor (Discontinued).....		\$52,436
M1622	CT5558E-HST Compact Tractor.....		\$56,291

Part Number	Description	Factory Installed Options	SLP in US \$
-------------	-------------	---------------------------	--------------

Tire Options

M_-R02-C01	Ag Tire: 8-16 6PR Front; 13.6-24 8PR Rear.....	\$789
	<i>Superior traction in muddy & soft soil, ideal for maximum pulling power & maneuverability in rugged conditions.</i>	
M_-R02-C02	Ind Tire (Standard): 10-16.5 6PR Front; 17.5-24 6PR Rear.....	\$592
	<i>Balanced combination of traction & surface area. Ideal for optimizing traction & minimizing ground disturbance.</i>	
M_-R02-C03	Turf Tire: 10-16.5 8PR Front; 17.5-24 8PR Rear.....	\$789
	<i>Maximizes surface area for minimal ground disturbance, ideal for protecting lawn/grass & icy conditions.</i>	
M_-R02-C07	Ind/Ag Hybrid Tire: 10-16.5 6PR Front; 17.5-24 6PR Rear.....	\$987
	<i>Premium, hybrid tread which combines traction of ag tire with high surface area & ride quality of the industrial tire.</i>	

Front End Loader - Bob-Tach

Includes quick attach front-end loader, hose kit, bucket level indicator, grille guard, mounting kit,
and 72" Bob-Tach bucket. (For maximum lift capacity, equip with rear
ballast box)

M_-A01-C01	FL9-5 Factory Installed.....	\$8,432
------------	------------------------------	---------

FEL Specs

	FL9-5
Maximum Lift Height to Bucket Pivot Pin.....	109"
Clearance with Level Bucket at Maximum Lift Height.....	101"
Clearance with Bucket Dumped at Maximum Lift Height.....	81"
Reach at Maximum Lift Height.....	7"
Length with Front End Loader & 3 Pt Hitch.....	178.6"
Bucket Dump Angle at Maximum Lift Height.....	59 degrees
Maximum Rollback Angle.....	37 degrees

Lift Capacity to Maximum Height at Bucket Pivot Pins.....	2346 lbs.
Loader Weight.....	1400 lbs
Breakout Force at Pivot Pin.....	4524 lbs
Standard Bucket Width.....	72"
Reach with Bucket on the Ground.....	70"

CT5545/CT5550/CT5555/CT5558

Compact Tractor

Part Number	Description	SLP in US \$
-------------	-------------	--------------

For current Dealer Installed Accessories pricing, reference BobQuote or Dealer Parts Department.

Cab Accessories		
7384249	Rear Wiper Kit.....	\$ _____
	Includes motor, wiper arm, wiper, switch and hardware. Install time: 2.0 hrs.	
7401630	Beacon Kit.....	\$ _____
	Includes lamp switch, wiring, hardware, beacon lamp and bracket. Install time: 1.0 hrs.	
7457482A	Bluetooth Radio Kit.....	\$ _____
	Includes radio, harness and hardware. Install time: 1.0 hrs.	

Hydraulic / Hitch Accessories		
7404544	Second Rear Remote Valve (Spring).....	\$ _____
	Includes second valve body, lever, cable and associated hardware. Install time: 1.5 hrs.	
7404545	Third Rear Remote Valve (Detent) (Requires Second Remote Valve).....	\$ _____
	Includes second valve body, lever, cable and associated hardware. Install time: 1.5 hrs.	

Ballast		
7402084	Front Weight Bracket (Not compatible with grille guard or FEL).....	\$ _____
	Includes weight bracket and associated hardware. Install time: 0.5 hrs.	
7158255	Suitcase Weights - 50 lbs (22.8 kg)	\$ _____
	Includes cast weight only. CT55xx can hold up to 6 weights. Bracket required.	

Cold Weather Accessories		
7401548	(FRV) Fuel Recirculation Valve Kit.....	\$ _____
	Includes valve, hoses, and clamps. Install time: 1.0 hrs.	
7388933	Block Heater.....	\$ _____
	Includes block heater and instructions. Install time: 1.0 hrs.	

Tire/Wheel Assemblies		
Bias Ply Ag (R1)		
7464585	8-16 6PR R-1, Front Left	\$ _____
7464584	8-16 6PR R-1, Front Right.....	\$ _____
46932167	13.6-24 8PR R-1, Rear Left.....	\$ _____
46932166	13.6-24 8PR R-1, Rear Right.....	\$ _____
Bias Ply Industrial/General Purpose (R4)		
46932170	10-16.5 6PR R-4, Front Left.....	\$ _____
46932169	10-16.5 6PR R-4, Front Right.....	\$ _____
46932156	17.5-24 6PR R-4, Rear Left.....	\$ _____
46932157	17.5-24 6PR R-4, Rear Right.....	\$ _____
Bias Ply Industrial/Ag Hybrid (R14)		
46985456	10-16.5 6PR R-4, Front Left.....	\$ _____
46985457	10-16.5 6PR R-4, Front Right.....	\$ _____
46985458	17.5-24 6PR R-4, Rear Left.....	\$ _____
46985455	17.5-24 6PR R-4, Rear Right.....	\$ _____
Bias Ply Turf (R3)		
46932168	10-6.5 8PR R-3, Front.....	\$ _____
46932158	17.5L-24 8PR R-3, Rear.....	\$ _____

Front-End Loader Accessories		
7393042	Bolt-on 72" Cutting Edge for FL9-5 (CT55xx).....	\$ _____
7417542	3rd Function Kit for FL9-5 (CT55xx).....	\$ _____
Includes flat face couplers (Pioneer couplers need to be ordered separately). Install time: 2.0 hrs.		
Additional Accessories		
7384239	Mid PTO Kit.....	\$ _____
Mid PTO assembly. Requires Mid PTO Lever. Install time: 1.5 hrs.		
7384240	Mid PTO Lever.....	\$ _____
Lever assembly. Install time: 0.25 hrs.		
7389556	Air Cleaner Inner Filter.....	\$ _____
Filter element. Install time: 0.1 hrs.		
7393120	Translation Kit.....	\$ _____
Includes decals, Operator's Handbook, Safety Manual, and Warranty Brochure. Install time: 0.25 hrs		